

Bit Sockets: Torx® Screw Driver

Cementex offers 1000V rated insulated bit tip sockets for use with insulated tools including ratchets, torque wrenches, extensions bars, T-Handled square drives, breaker bars, etc.

Cementex's unique coating technique allows the socket to be shaped in a way that the insulation is slimmer at the point of contact with the nut or bolt. This allows Cementex insulated sockets to access equipment where other manufacturer's sockets won't fit.



1/4" Square Drive: Torx® Tip Screwdriver Bit Options

Size	3" Length		6" Length	
	Booted	Flush Connect	Booted	Flush Connect
T8	IT14-T8	IT14-T8 WO	IT14-T8XL	IT14-T8XL WO
T10	IT14-T10	IT14-T10 WO	IT14-T10XL	IT14-T10XL WO
T15	IT14-T15	IT14-T15 WO	IT14-T15XL	IT14-T15XL WO
T20	IT14-T20	IT14-T20 WO	IT14-T20XL	IT14-T20XL WO
T25	IT14-T25	IT14-T25 WO	IT14-T25XL	IT14-T25XL WO
T27	IT14-T27	IT14-T27 WO	IT14-T27XL	IT14-T27XL WO
T30	IT14-T30	IT14-T30 WO	IT14-T30XL	IT14-T30XL WO
T40	IT14-T40	IT14-T40 WO	IT14-T40XL	IT14-T40XL WO
T45	IT14-T45	IT14-T45 WO	IT14-T45XL	IT14-T45XL WO
T50	IT14-T50	IT14-T50 WO	IT14-T50XL	IT14-T50XL WO
T55	IT14-T55	IT14-T55 WO	IT14-T55XL	IT14-T55XL WO



Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V

3/8" Square Drive: Torx® Tip Screwdriver Bit Options

Size	3" Length		6" Length	
	Booted	Flush Connect	Booted	Flush Connect
T8	IT38-T8	IT38-T8 WO	IT38-T8XL	IT38-T8XL WO
T10	IT38-T10	IT38-T10 WO	IT38-T10XL	IT38-T10XL WO
T15	IT38-T15	IT38-T15 WO	IT38-T15XL	IT38-T15XL WO
T20	IT38-T20	IT38-T20 WO	IT38-T20XL	IT38-T20XL WO
T25	IT38-T25	IT38-T25 WO	IT38-T25XL	IT38-T25XL WO
T27	IT38-T27	IT38-T27 WO	IT38-T27XL	IT38-T27XL WO
T30	IT38-T30	IT38-T30 WO	IT38-T30XL	IT38-T30XL WO
T40	IT38-T40	IT38-T40 WO	IT38-T40XL	IT38-T40XL WO
T45	IT38-T45	IT38-T45 WO	IT38-T45XL	IT38-T45XL WO
T50	IT38-T50	IT38-T50 WO	IT38-T50XL	IT38-T50XL WO
T55	IT38-T55	IT38-T55 WO	IT38-T55XL	IT38-T55XL WO



1/2" Square Drive: Torx® Tip Screwdriver Bit Options

Size	3" Length		6" Length	
	Booted	Flush Connect	Booted	Flush Connect
T8	IT12-T8	IT12-T8 WO	IT12-T8XL	IT12-T8XL WO
T10	IT12-T10	IT12-T10 WO	IT12-T10XL	IT12-T10XL WO
T15	IT12-T15	IT12-T15 WO	IT12-T15XL	IT12-T15XL WO
T20	IT12-T20	IT12-T20 WO	IT12-T20XL	IT12-T20XL WO
T25	IT12-T25	IT12-T25 WO	IT12-T25XL	IT12-T25XL WO
T27	IT12-T27	IT12-T27 WO	IT12-T27XL	IT12-T27XL WO
T30	IT12-T30	IT12-T30 WO	IT12-T30XL	IT12-T30XL WO
T40	IT12-T40	IT12-T40 WO	IT12-T40XL	IT12-T40XL WO
T45	IT12-T45	IT12-T45 WO	IT12-T45XL	IT12-T45XL WO
T50	IT12-T50	IT12-T50 WO	IT12-T50XL	IT12-T50XL WO
T55	IT12-T55	IT12-T55 WO	IT12-T55XL	IT12-T55XL WO

Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V

