

Hex "L" Long Arm Allen Wrenches



IHW-120

- Hardened American Steel
- Cementex double insulation system utilizes superior raw material and insulating process to provide the safest Voltage Rated tools possible

Wide range of sizes and lengths available

SAE Options	
Part Number	Size
IHW-116	1/16"
IHW-564	5/64"
IHW-332	3/32"
IHW-764	7/64"
IHW-180	1/8"
IHW-964	9/64"
IHW-532	5/32"
IHW-316	3/16"
IHW-732	7/32"
IHW-140	1/4"
IHW-516	5/16"
IHW-380	3/8"
IHW-716	7/16"
IHW-120	1/2"
IHW-916	9/16"
IHW-580	5/8"
IHW-340	3/4"

Metric Options	
Part Number	Size
IHW-1.5M	1.5mm
IHW-2M	2mm
IHW-2.5M	2.5mm
IHW-3M	3mm
IHW-3.5M	3.5mm
IHW-4M	4mm
IHW-5M	5mm
IHW-5.5M	5.5mm
IHW-6M	6mm
IHW-7M	7mm
IHW-8M	8mm
IHW-9M	9mm
IHW-10M	10mm
IHW-11M	11mm
IHW-12M	12mm
IHW-13M	13mm
IHW-14M	14mm
IHW-17M	17mm
IHW-19M	19mm
IHW-22M	22mm
IHW-24M	24mm

Custom construction available upon request



Cementex double-insulated tools:

- Comply with the IEC 60900 standard
- Comply with ASTM F1505 standard
- Help you meet the requirements of OSHA Safety Related Work Practices, NFPA 70E Standard and CSA-Z462

Cementex double-insulated tools are:

- Tested to 10,000 VAC and rated for 1,000 VAC/1,500DC when working on live parts
- Manufactured in the U.S.A. with both US and globally sourced materials
- Marked with the international safety symbol —  1000V